



VENUS T5 mini

5-Bay SATA RAID Enclosure

- EZ-RAID setup DIP switch
- Support Hot Swap and Hot Spare on RAID
- Supports JBOD, Clone, RAID 0, 1, 3, 5 and 10
- SATA II Port Multiplier backplane
- Management Console (GUI)
- JMB393 Hardware-accelerated RAID Engine
(No drivers or BIOS required for RAID and compatible to x86/x64 platforms)



EZ-RAID setup switch does not required any drivers or BIOS for RAID operation.



Software Management Console (GUI)

- Event logging
- Remote monitoring
- Email notification (Hardware Failure)
- JBOD, Clone, RAID 0, 1, 3, 5 and 10
- Support on-line Auto-Rebuild (200GB/hour)
- Support Hot Swap and Hot Spare on RAID



Hardware RAID
JMB393 Chipset

Compat and Stylist design give you the best storage enclosure to store your Video and Audio files. T5J mini takes up less space on your desk plus easy to carry around for your business travel.



POWER ADAPTER
20w (100-240Vac) 50/60Hz



REAR VIEW
(EZ-RAID Switch)

VENUS T5 (DS-2250J)

Capacity:*	2.5TB
Port Multiplier Host Interface:	eSATA (3.0Gbit/s)
Disk Interface:	SATA connector
Disk Drive Tested:**	160GB to 500GB HDD (9.5mm)
Interface Transfer Rate:***	1.5Gbit/s & 3.0Gbit/s
Software:****	Management Console (GUI)
Supported RAID levels:	JBOD, RAID 0, 1, 3, 5 and 10
Supported OS (32-bit/64-bit):	Windows 2000/2003/XP/Vista/Win7 Ultimate / Mac OS 10.4.x or later
I/O Control:	Power and Mult-Colored HDD LED
Cooling:	5x5cm Fan (ball-bearing)
Operating Temperature:	5° to 35° C, Humidity 20 to 80% No Condensation
Power Supply:	20w, AC (100-240Vac) 50/60Hz Power Adapter
Material/Color:	Brush Aluminum Anodized Black
Dimensions (LxWxH):	5.5" x 3.1" x 4.9"
Weight:	1.35 lbs (net wt.)
Warranty:	1 year



VENUS T5

* 1GB (gigabyte) = 1 billion bytes. 1TB (terabyte) = 1000GB. Actual capacity varies depending on operating environment. (typically 5-10% less).

** Tested with SATA I/II (Seagate, Hitachi and Western Digital)

*** Specifications vary depending upon the selected RAID configuration (storage policy). Maximum capacities and sustained transfer rates were rated in (RAID 0)

**** Configuration Manager and Firmware updates provided by www.SiliconImage.com (Windows XP will not recognize single volumes greater than 2TB).

VENUS DS2, DS3, DS5, DS3R, DS3RPRO, T4, T4U, T4S, T5S, and T5J are trademarks of American Media Systems, Inc.

©2010 American Media Systems, Inc. (AMSElectronics). Other names or brands herein may be trademarks or registered trademarks of their respective owners.

