

VENUS eS2

SATA RAID STORAGE ENCLOSURE | RAID 0, 1 and JBOD + SAFE33/SAFE50



Fast USB 2.0 /eSATA interface with integrated RAID Technology RAID 0, 1 and JBOD + SAFE33/SAFE50 option. eS2 is perfect companion, product for DVD authoring 2D/3D animation, audio editing, streaming video and for system backup. You can trust eS2 for your storage protection on your digital photos, MP3s and other important files that you cannot be without.

TRANSFER RATE COMPARISON (Source: AMS Test Lab)

USB 2.0	Up to 34MB/s*
SATA I /SATA II	Up to 150/300MB/s**

MEGABYTES PER SECOND

* Performance may vary depending on user's data and computer configuration
** Performance may vary depending on SATA controller and computer configuration



USB 2.0 + eSATA



Trayless design

Model	VENUS DS-312SUES (Black)	
Storage	HDD Bays	Hot-Swap x2 bays of 3.5" SATA HD
	HDD Capacity	Up to 1TB per SATA drive Works with single HD
RAID Support		Spanning (RAID 0) Stripping (RAID 1)
		Expansion (JBOD)
		Mirror (RAID 1) SAFE33 and SAFE50
User Interface	Easy RAID setup switch for PC and Mac	
Connector Interface	USB 2.0 x1 + eSATA x1 port* (see SteelVine 57xx Hardware compatibility list)	
Indicators	Power, HD-1 and HD-2 LEDs	
Switch	Power switch and RAID setup Dial switch	
Power Supply	Input: 100-240Vac, 1.2A(Max), 50-60Hz / Output: 85w (5V/2A, 12V/2A)	
Cooling Fan	8cm Ball-Bearing Fan	
Material	Aluminum/Metal, ABS plastic	
Dimension	8.5(L) x 5.2(W) x 3.5(H) inches	
Warranty	1 Year	

Hardware Spec	Silicon Image 5744 Storage Processor
SATA capacity	SATA I/II (160G, 200G, 250G, 300G, 400G, 500G, 750G, 1TB, 2TB)

Package Contents

DS-312SUES x 1 *(HDD not included)
eSATA x1 and USB 2.0 x1 Cables
Power Adapter and cord x1
User manual and driver CD x1



American Media Systems, Inc. (AMSelectronics)
E-mail: Techsupport@amselectronics.com

* Information is subject to change without notice. All other product names mentioned are trademarks or registered trademarks of their respective owners.